

# Universal Socket Connectivity Selector Guide

Multi-Tech's **Universal Socket** flexible comm-port architecture provides cellular, Ethernet, PSTN, Wi-Fi\* or Bluetooth\* socket connectivity with interchangeable communications devices. This means you can utilize one system design and populate it with the appropriate connectivity option. Now you can provide a full-line of connectivity by simply dropping in the communications device of choice. In addition, you are assured a seamless migration to future technologies – simply upgrade your connectivity module and keep your product current and design intact.

(I/O) Tip	1	○		○	64	SPKR (O)
(I/O) Ring	2	○		○	63	GND (O)
Safety Void	3	×		○	62	MICV (I)
(O) TX+	4	○		○	61	VCC (I)
(O) TX-	5	○		○	60	-LED SPD (O)
(I) RX+	6	○		○	59	-LED COL (O)
(I) RX-	7	○		○	58	-LED LINK (O)
Safety Void	8	×		○	57	-LED ACT (O)
	9			○	56	-LED FDX (O)
	10			○	55	
(O) TXCLK	11			○	54	
(O) RXCLK	12	○		○	53	
	13			○	52	
	14			○	51	GPIO (I/O)
	15			○	50	GPIO (I/O)
	16			○	49	GPIO (I/O)
	17			○	48	GPIO (I/O)
	18			○	47	
	19			○	46	
	20			○	45	
(I)	21			○	44	
(I) Mic+	22	○		○	43	SPK+ (O)
(I) Mic-	23	○		○	42	SPK- (O)
(I) -Reset	24	○		○	41	GND (I)
(I) USB_VBUS	25	○		○	40	-DTR (I)
(I) GND	26	○		○	39	-DCD (O)
(I/O) USB_DP	27	○		○	38	-CTS (O)
(I/O) USB_DN	28	○		○	37	-DSR (O)
(O) LED DCD	29	○		○	36	-RI (O)
(O) LED RX	30	○		○	35	-TXD (I)
(O) LED DTR	31	○		○	34	-RXD (O)
(O) LED TX	32	○		○	33	-RTS (I)

## Universal Socket

SocketModem iCell  
 SocketModem Cell  
 SocketModem EDGE  
 SocketModem  
 SocketModem IP  
 SocketEthernet IP  
 SocketWireless Bluetooth  
 SocketWireless Wi-Fi

Multi-Tech's intelligent **Universal IP**® consists of a common set of TCP/IP networking protocols and machine-to-machine (M2M) applications implemented using a standard AT command interface. Universal IP allows developers to write their host application one time while having the freedom to select from a growing number of Universal Socket communication devices and use the latest 2G and 3G technologies.


The **Universal Socket Developer's Kit** allows you to plug in the communications device and use it for testing, programming and evaluation. Contact your local Multi-Tech distributor or sales representative for complete details or visit [www.multitech.com/pdfs/devkit.go](http://www.multitech.com/pdfs/devkit.go)

Our **Universal Socket Developer's Guide** assists you in evaluating the embedded family of connectivity solutions as you consider the different options for current, as well as, future requirements of your product strategy. To obtain a guide, contact Multi-Tech directly or visit our website at [www.multitech.com/primers/universal\\_socket.go](http://www.multitech.com/primers/universal_socket.go)




## SocketModem® iCell Intelligent cellular modems

- 2G and 3G, GSM and CDMA
- Serial only or Serial and USB
- GPS
- Persistent connectivity
- GPIO




## SocketModem® Cell Cellular modems

- 2G and 3G, GSM and CDMA
- Serial or USB interface
- Embedded TCP/IP stack



## SocketModem® & SocketModem® IP Global\*

- V.92/56K data rates
- V.34/33.6K fax
- Serial or parallel interface
- 3.3 or 5V models
- Universal IP available



## SocketEthernet IP® Serial-to-Ethernet device server

- 10/100BaseT Ethernet interface
- Medical/high voltage isolation (EN60601)
- Multiple LED driver outputs



## SocketWireless® Wi-Fi® Serial-to-Wi-Fi device server

- 802.11b/g wireless networking
- Wi-Fi security using WEP, WPA and WPA2
- Supports ad-hoc and infrastructure mode
- Serial interface speeds to 921.6K bps



## SocketWireless® Bluetooth® Serial-to-Bluetooth device server

- 100 meter (330 ft.) range
- Class 1 Bluetooth V2.0 compliant
- Point-to-point and multi-point communications

\* Multi-Tech's global modems are designed for worldwide applications with approvals in many countries. This means one SKU can ship virtually anywhere.

## Embedded Analog Modems

Complete, ready-to-integrate voice/data/fax modems.

Models	MT2492SMI-xx	MT9234SMI-xx	MT5692SMI-xx
<b>Telecom Approvals</b>			
Global		X	X
<b>Interface</b>			
Serial	X	X	X
Parallel		X	X
<b>Power</b>			
3.3 Volt	X	X	X
5 Volt	X	X	X
<b>Maximum Data Rate</b>			
V.92/56K	X	X	X
V.34/33.6K	X	X	X
V.22bis/2400 baud	X		
<b>Fax Capability</b>			
V.34 Fax		X	
V.17 Fax		X	X
V.29/V.27/V.21 Fax		X	X
Fax Class 1		X	X
Fax Class 1.0		X	X
Fax Class 2		X	
Fax Class 2.0/2.1		X	
Fax Compression (MH, MR, MMR)		X	
Error Correction Mode (ECM)		X	
<b>Memory Type</b>			
Flash + RAM		X	
Masked ROM	X		X
<b>Features</b>			
11-bit Mode		X	
U.S. Caller ID	X	X	X
Leased Line		X	
V.22bis Fast Connect	X	X	X
FastPOS (V.29)			X
Callback Security		X	
Industrial Temp Range		X	X
Medical Isolation		X	
LED Pin Outputs		X	X
Extension Pickup Detection	X		X
Remote Hang-up Detection	X		X
Line-in-use Detection	X		X
Digital PBX Detection & Protection	X		X
Voice Record & Playback (TAM)		X	X
Speakerphone I/O			X

See datasheets for more specifications and ordering part numbers.

Features and specifications are subject to change without notice.

**Trademarks / Registered Trademarks:** SocketModem, SocketWireless, SocketEthernet IP, Universal IP, Multi-Tech, and the Multi-Tech logo: Multi-Tech Systems, Inc. / All other products and technologies are the trademarks or registered trademarks of their respective holders.

### World Headquarters

Tel: (763) 785-3500  
(800) 328-9717  
www.multitech.com

### EMEA Headquarters

Multi-Tech Systems (EMEA)  
United Kingdom  
Tel: +(44) 118 959 7774

## Embedded Cellular Modems

Complete, ready-to-integrate and carrier-approved cellular modems.

Models	MTSMC-H4-xx	MTSMC-EV2-xx	MTSMC-E1-xx	MTSMC-G2-xx	MTSMC-C1-xx	MTSMC-H3-xx	MTSMC-EV1-xx
Network Type	HSPA 7.2	EV-DO Rev A	EDGE Class 12	GPRS Class 10	CDMA2000 1xRIT	HSPA 7.2	EV-DO Rev A
Dual-band CDMA (800/1900 MHz)		X			X		X
Quad-band GSM (850/900/1800/1900 MHz)	X		X	X		X	
Tri-band HSPA (850/1900/2100 MHz)	X						
Quad-band HSPA (850/900/1900/2100 MHz)						X	
Maximum Packet Data Rate - Download	7.2M	3.1M	240K	85.6K	153.6K	7.2M	3.1M
Maximum Packet Data Rate - Upload	5.76M	1.8M	240K	85.6K	153.6K	5.76M	1.8M
Short Message Service	X	X	X	X	X	X	X
14.4K Circuit-switched Data	X	X	X	X	X	X	
Maximum DTE Speed (Serial)	921.6K	921.6K	460K	115.2K	230K	921.6K	921.6K
USB 2.0 Full Speed	X	X				X	X
AT Command Compatible	X	X	X	X	X	X	X
UFL Antenna Connector	X	X		X	X	X	X
MMCX Antenna Connector			X				
5 VDC Operation	X	X	X	X	X	X	X
GPS Tracking	X	X		X	X		

## Embedded Universal IP®

Models	MT5692SMI-IP-xx	MT1005EM-IP	MT810SWM-IP	MTSMC-H4-IP/GP	MTSMC-EV2-IP/GP	MTSMC-G2-IP/GP	MTSMC-C1-IP/GP	MTSMC-H3-IP	MTSMC-EV1-IP
<b>Network Protocol Support</b>									
ARP		X	X						
DHCP Client		X	X						
DNS	X	X	X	X	X	X	X	X	X
FTP Client	X	X	X	X	X	X	X	X	X
ICMP (Ping)	X	X	X	X	X	X	X	X	X
POP 3 (Receive mail)	X	X	X	X	X	X	X	X	X
PPP (Dial-out)	X			X	X	X	X	X	X
SMTP (Send mail)	X	X	X	X	X	X	X	X	X
TCP Socket	X	X	X	X	X	X	X	X	X
UDP Socket	X	X	X	X	X	X	X	X	X
Telnet Server		X	X						
<b>M2M Features</b>									
Automatic/Persistent Connect	X	X	X	X	X	X	X	X	X
Device Monitor	X	X	X	X	X	X	X	X	X
Modem Emulation	X	X	X	X	X	X	X	X	X
Ping/TCP Keep Alive	X	X	X	X	X	X	X	X	X
Wake-up on Ring	X			X	X	X	X	X	X
Wake-up on Caller ID	X			X	X	X	X	X	X
<b>Authentication Protocols</b>									
CHAP	X			X	X	X	X	X	X
PAP	X			X	X	X	X	X	X